

Software design of the 3d BEPS3 PIC codes

Viktor K. Decyk

Department of Physics and Astronomy

University of California, Los Angeles

Los Angeles, California 90095-1547

Introduction

This Particle-in-Cell (PIC) code is intended for research and teaching in plasma physics. Plasmas are ionized gases interacting with electromagnetic fields they generate. It is an example of a many body system described by statistical mechanics. PIC codes model plasmas as discrete particles and this code serves as a lab to perform numerical experiments.

This software consists of three separate Particle-in-Cell codes: an electrostatic, and electromagnetic, and a darwin code. They are based on the 3d OpenMP/MPI skeleton codes (mppic3, mpbpic3, mpdpic3) available at: <http://picksc.idre.ucla.edu/software/skeleton-code/>, with additional diagnostics and initial conditions added. The codes are written in layers. They are intended to be run on a large variety of platforms, from student laptops to supercomputers. The lowest, most compute intensive layer is mostly written in a Fortran77 subset of Fortran90. This layer uses only basic types, without array syntax and compiles to very fast code. It is easy to replace this layer with a C language layer. It contains about 200 procedures and 31,000 lines of code. The middle layer consists of Fortran90 wrappers, which simplifies the argument lists, introduces some polymorphism with case statements, adds safety checks, and is designed to be easily called from Python. It consists of 160 procedures and 5,500 lines of code organized in 11 libraries. The upper layer consists of 3 high level libraries which conform to the Fortran2003 standard and allows implementation of such features as object oriented programming, interoperability with C, and stream IO. The three high level libraries currently contain about 11 procedures and 600 lines of code.

Low level libraries

The libraries are organized according the type of code, electrostatic, electromagnetic, and darwin. Eight of the libraries are used by all 3 codes:

```
libmpinit3.f: initializes particles
libmppush3.f: pushes electrostatic particles, deposits charge,
               and provides utility functions
```

`libmpsort3.f`: reorders particles for parallelization
`libmpgard3.f`: provides functions to process guard cells
`libmpfield3.f`: provides spectral field solvers and diagnostics
`libmpfft3.f`: provides 3D FFTs for scalar and vector arrays
`libmpdiag3.f`: provides diagnostic procedures such as
 distribution functions, frequency analysis, and
 others
`mpplib3.f90` provides communications procedures using MPI/OpenMP

Two of the libraries are used by the electromagnetic and darwin codes:

`libmpcurd3.f`: deposits current density
`libmpbpush3.f`: pushes electromagnetic particles

One library is used by darwin code:

`libmpdpush3.f`: deposits time derivative of current density

Comments at the beginning of each library describe what each individual procedure does and comments at the beginning of each function give additional details as well as information about the input and output variables.

Middle level libraries

The eleven middle level libraries provide an easier to use interface to the low level libraries and can be called by Python. They provide error checking but do not process errors (which may need to be processed in another language.) They also provide some level of polymorphism, such as whether a relativistic version of procedures should be used.

The middle level wrapper libraries have the same structure as the low level libraries. They are written to conform to the Fortran 90 standard. The names are similar, except that they usually start with `mod...` and end in `...f90` instead of `lib...` and `...f`. For example, the wrapper for `libmpinit3.f` is `modmpinit3.f90`. In addition, there are libraries that provide interfaces to the low level procedures to support argument checking for procedures (similar to header files in C). Their names are the same as the low level libraries, except they terminate with `_h.f90` instead of `.f`.

Comments at the beginning of each library describe what each individual procedure does and what low level procedures are called.

The Python wrappers can be created automatically from the middle layer by the numpy tool `f2py`. This required that the middle layer avoid certain Fortran90 language features,

such as derived types and function overloading, and required that they provide the `intent` attribute for dummy arguments. The attribute `intent(inout)` was used whenever a variable or array was modified, and `intent(in)` otherwise. All communication between Python and Fortran will occur only in the middle layer,

Input to the codes currently consists of about 190 `namelist` variables in 4 different `namelists`. The variables are defined and default values are given in the Fortran90 file `input3mod.f90`, which defines a module called `in3`. The `namelist input3` is used by all three codes. The `namelist input3b` is used by the electromagnetic and darwin codes, and the `namelist input3d` is used only by the darwin code. There is also a `namelist ions3` which is used by all 3 codes if ions are mobile. Comments in the module `input3mod.f90` give short descriptions of each input variable and its usage.

High Level libraries

Three Fortran2003 high level libraries are defined. The main purpose of these libraries is to encapsulate the data and the main steps of the PIC code and the major diagnostics. Currently, only the restart procedures are encapsulated.

The library `mpsimul3.f03` is used by all three codes. This library defines a module `mpsimul3` which provides support for the following:

1. Support for restart files for electrostatic code

The library `mpbsimul3.f03` is used by the electromagnetic and darwin codes. This library defines a module `mpbsimul3` which provides support for the following:

1. Support for restart files for electromagnetic code

The library `mpdsimul3.f03` is used by the darwin code. This library defines a module `mpdsimul3` which provides support for the following:

1. Support for restart files for darwin code

Comments at the beginning of each library describe what each individual procedure does.

Main codes

Three Fortran90 main codes were written for each code, `mpbeps3.f90`, `mpbbeeps3.f90`, and `mpdbeeps3.f90`. The libraries and main codes are compiled by a Makefile.