

```

/*-----*/
/* Skeleton 2D Electrostatic OpenMP PIC code */
/* written by Viktor K. Decyk, UCLA */
#include <stdlib.h>
#include <stdio.h>
#include <complex.h>
#include <sys/time.h>
#include "mpush2.h"
#include "omplib.h"

void dtimer(double *time, struct timeval *itime, int icntrl);

int main(int argc, char *argv[]) {
    int indx = 9, indy = 9;
    int npx = 3072, npy = 3072;
    int ndim = 2;
    float tend = 10.0, dt = 0.1, qme = -1.0;
    float vtx = 1.0, vty = 1.0, vx0 = 0.0, vy0 = 0.0;
    float ax = .912871, ay = .912871;
    /* idimp = dimension of phase space = 4 */
    int idimp = 4, ipbc = 1;
    float wke = 0.0, we = 0.0, wt = 0.0;
    /* sorting tiles, should be less than or equal to 32 */
    int mx = 16, my = 16;
    /* fraction of extra particles needed for particle management */
    float xtras = 0.2;
    /* declare scalars for standard code */
    int j;
    int np, nx, ny, nxh, nyh, nxe, nye, nxeh, nxyh, nxhy;
    int mx1, my1, mxy1, ntime, nloop, isign;
    float qbme, affp;

    /* declare scalars for OpenMP code */
    int nppmx, nppmx0, ntmax, npbm, irc;
    int nvp;

    /* declare arrays for standard code */
    float *part = NULL;
    float *qe = NULL;
    float *fxye = NULL;
    float complex *ffc = NULL;
    int *mixup = NULL;
    float complex *sct = NULL;

    /* declare arrays for OpenMP (tiled) code */
    float *ppart = NULL, *ppbuff = NULL;
    int *kpbc = NULL;
    int *ncl = NULL;
    int *ihole = NULL;

    /* declare and initialize timing data */
    float time;
    struct timeval itime;
    float tdpost = 0.0, tguard = 0.0, tfft = 0.0, tfield = 0.0;

```

```

float tpush = 0.0, tsort = 0.0;
double dtime;

irc = 0;
/* nvp = number of shared memory nodes (0=default) */
nvp = 0;
/* printf("enter number of nodes:\n"); */
/* scanf("%i",&nvp); */
/* initialize for shared memory parallel processing */
cinit_omp(nvp);

/* initialize scalars for standard code */
np = npx*ncpy; nx = 1L<<indx; ny = 1L<<indy; nxh = nx/2; nyh = ny/2;
nxe = nx + 2; nye = ny + 1; nxeh = nxe/2;
nxyh = (nx > ny ? nx : ny)/2; nxhy = nxh > ny ? nxh : ny;
mx1 = (nx - 1)/mx + 1; my1 = (ny - 1)/my + 1; mxy1 = mx1*my1;
nloop = tend/dt + .0001; ntime = 0;
qbme = qme;
affp = (float) (nx*ny)/(float ) np;

/* allocate and initialize data for standard code */
part = (float *) malloc(idimp*np*sizeof(float));
qe = (float *) malloc(nxe*nye*sizeof(float));
fxye = (float *) malloc(ndim*nxe*nye*sizeof(float));
ffc = (float complex *) malloc(nxh*nyh*sizeof(float complex));
mixup = (int *) malloc(nxhy*sizeof(int));
sct = (float complex *) malloc(nxyh*sizeof(float complex));
kp1c = (int *) malloc(mxy1*sizeof(int));

/* prepare fft tables */
cwfft2rinit(mixup,sct,indx,indy,nxhy,nxyh);
/* calculate form factors */
isign = 0;
cmppois22((float complex *)qe,(float complex *)fxye,isign,ffc,ax,ay,
          affp,&we,nx,ny,nxeh,nye,nxh,nyh);
/* initialize electrons */
cdistr2(part,vtx,vty,vx0,vy0,npx,ncpy,idimp,np,nx,ny,ipbc);

/* find number of particles in each of mx, my tiles: updates kp1c, nppmx */
cdblkp2l(part,kp1c,&nppmx,idimp,np,mx,my,mx1,mxy1,&irc);
if (irc != 0) {
    printf("cdblkp2l error, irc=%d\n",irc);
    exit(1);
}
/* allocate vector particle data */
nppmx0 = (1.0 + xtras)*nppmx;
ntmax = xtras*nppmx;
npbm1x = xtras*nppmx;
ppart = (float *) malloc(idimp*nppmx0*mxy1*sizeof(float));
ppbuff = (float *) malloc(idimp*npbm1x*mxy1*sizeof(float));
ncl = (int *) malloc(8*mxy1*sizeof(int));
ihole = (int *) malloc(2*(ntmax+1)*mxy1*sizeof(int));
/* copy ordered particle data for OpenMP */
cppmovin2l(part,ppart,kp1c,nppmx0,idimp,np,mx,my,mx1,mxy1,&irc);

```

```

    if (irc != 0) {
        printf("cppmovin2l overflow error, irc=%d\n",irc);
        exit(1);
    }
/* sanity check */
cppcheck2l(ppart,kpic,idimp,nppmx0,nx,ny,mx,my,mx1,my1,&irc);
if (irc != 0) {
    printf("%d, cppcheck2l error: irc=%d\n",ntime,irc);
    exit(1);
}

/* * * * start main iteration loop * * * */

L500: if (nloop <= ntime)
    goto L2000;
/*    printf("ntime = %i\n",ntime); */

/* deposit charge with OpenMP: updates qe */
    dtimer(&dtime,&itime,-1);
    for (j = 0; j < nxe*nye; j++) {
        qe[j] = 0.0;
    }
    cgppost2l(ppart,qe,kpic,qme,nppmx0,idimp,mx,my,nxe,nye,mx1,my1);
    dtimer(&dtime,&itime,1);
    time = (float) dtime;
    tdpost += time;

/* add guard cells with OpenMP: updates qe */
    dtimer(&dtime,&itime,-1);
    caguard2l(qe,nx,ny,nxe,nye);
    dtimer(&dtime,&itime,1);
    time = (float) dtime;
    tguard += time;

/* transform charge to fourier space with OpenMP: updates qe */
    dtimer(&dtime,&itime,-1);
    isign = -1;
    cwfft2rmx((float complex *)qe,isign,mixup,sct,indx,indy,nxeh,
        nye,nxhy,nxyh);
    dtimer(&dtime,&itime,1);
    time = (float) dtime;
    tffft += time;

/* calculate force/charge in fourier space with OpenMP: updates fxye, we */
    dtimer(&dtime,&itime,-1);
    isign = -1;
    cmpois22((float complex *)qe,(float complex *)fxye,isign,ffc,ax,
        ay,affp,&we,nx,ny,nxeh,nye,nxh,nyh);
    dtimer(&dtime,&itime,1);
    time = (float) dtime;
    tfield += time;

/* transform force to real space with OpenMP: updates fxye */
    dtimer(&dtime,&itime,-1);

```

```

        isign = 1;
        cwfft2rm2((float complex *)fxye, isign, mixup, sct, indx, indy, nxeh,
                nye, nxhy, nxyh);

        dtimer(&dtype, &itime, 1);
        time = (float) dtype;
        tfft += time;

/* copy guard cells with OpenMP: updates fxye */
        dtimer(&dtype, &itime, -1);
        ccguard2l(fxye, nx, ny, nxe, nye);
        dtimer(&dtype, &itime, 1);
        time = (float) dtype;
        tguard += time;

/* push particles with OpenMP: updates ppart, ncl, ihole, wke, irc */
        wke = 0.0;
        dtimer(&dtype, &itime, -1);
        cgppushf2l(ppart, fxye, kplic, ncl, ihole, qbme, dt, &wke, idimp, nppmx0,
                nx, ny, mx, my, nxe, nye, mx1, mxy1, ntmax, &irc);
        dtimer(&dtype, &itime, 1);
        time = (float) dtype;
        tpush += time;
        if (irc != 0) {
            printf("cgppushf2l error: irc=%d\n", irc);
            exit(1);
        }

/* reorder particles by tile with OpenMP: */
/* updates ppart, ppbuff, kplic, ncl, ihole, and irc */
        dtimer(&dtype, &itime, -1);
        cpporderf2l(ppart, ppbuff, kplic, ncl, ihole, idimp, nppmx0, mx1, my1,
                npbm, ntmax, &irc);
        dtimer(&dtype, &itime, 1);
        time = (float) dtype;
        tsort += time;
        if (irc != 0) {
            printf("cpporderf2l error: ntmax, irc=%d,%d\n", ntmax, irc);
            exit(1);
        }

        if (ntime==0) {
            printf("Initial Field, Kinetic and Total Energies:\n");
            printf("%e %e %e\n", we, wke, wke+we);
        }
        ntime += 1;
        goto L500;
L2000:

/* * * * end main iteration loop * * * */

        printf("ntime = %i\n", ntime);
        printf("Final Field, Kinetic and Total Energies:\n");
        printf("%e %e %e\n", we, wke, wke+we);

```

```

printf("\n");
printf("deposit time = %f\n",tdpost);
printf("guard time = %f\n",tguard);
printf("solver time = %f\n",tfield);
printf("fft time = %f\n",tfft);
printf("push time = %f\n",tpush);
printf("sort time = %f\n",tsort);
tfield += tguard + tfft;
printf("total solver time = %f\n",tfield);
time = tdpost + tpush + tsort;
printf("total particle time = %f\n",time);
wt = time + tfield;
printf("total time = %f\n",wt);
printf("\n");

wt = 1.0e+09/(((float) nloop)*((float) np));
printf("Push Time (nsec) = %f\n",tpush*wt);
printf("Deposit Time (nsec) = %f\n",tdpost*wt);
printf("Sort Time (nsec) = %f\n",tsort*wt);
printf("Total Particle Time (nsec) = %f\n",time*wt);
printf("\n");

return 0;
}

```